

PATENT SPECIFICATION

(11)

1 495 436

1 495 436

(21) Application No. 24542/75 (22) Filed 7 June 1975

(23) Complete Specification filed 10 May 1976

(44) Complete Specification published 21 Dec. 1977

(51) INT. CL.² A63B 23/06

(52) Index at acceptance
A6M 8L2 8LY



SCIENCE REFERENCE LIBRARY

(54) IMPROVEMENTS IN EXERCISING APPARATUS

(71) I, DAVID JAMES GIBBS, a British Subject, of 6, Linden Close, Green Park, Wootton Bassett, Swindon, Wiltshire, do hereby declare the invention, for which I pray that a patent may be granted to me, and the method by which it is to be performed, to be particularly described in and by the following statement:—

This invention relates to exercising apparatus and is particularly concerned with apparatus for use by patients in hospitals for physiotherapeutic purposes and by persons wishes to attain or retain physical fitness.

Exercising apparatus is available which includes a supporting base carrying a pair of spaced rollers around which an endless belt is entrained, a person standing on the belt holding a pair of hand grips and effectively "walking" along the belt at a rate determined by the output speed of an electric motor which drives one of the rollers. Such apparatus is extremely useful but it is large and expensive. It is accordingly an object of the invention to provide exercising apparatus which is of compact robust construction and relatively inexpensive to manufacture.

According to the invention there is provided exercising apparatus comprising a supporting framework including a platform and hand-grip means for gripping by a person standing on the platform, said platform having a presented surface afforded by a multiplicity of independently rotatable rollers comprising a plurality of rows of rollers with each row of rollers containing a plurality of rollers and the rollers being arranged for rotation about substantially horizontal axes.

The area occupied by the rollers is conveniently of the order of one foot in width and two feet three inches in length, each roller having a length and a diameter of, for example, seven eighths of an inch. Dur-

ing movement of the feet of a person standing on the platform, the rates of rotation of the different rollers will not be the same because of the different modes of movement of the various parts of a person's foot. It is, therefore, important that there should be a large number of rollers.

Means are preferably provided for adjusting the inclination of the platform to the horizontal, the arrangement being such that the rate at which the user of the apparatus has to move to maintain his position on the rollers is dependent on the inclination of the platform. Said adjustment means may comprise a stepped base which is provided with formations for engagement with cooperative formations on the underside of the platform. The formations on the underside of the platform are preferably recesses and the formations on the base are preferably a plurality of projections on each step.

In order to facilitate use of the apparatus in confined spaces and to enable transport and storage of the apparatus to be carried out more easily, the framework of the apparatus conveniently comprises a plurality of dismantlable components, the hand-grip means being afforded by a generally U-shaped member having legs which clip into and are held within sockets disposed outwardly of a peripheral frame around the rollers. Provision may be made for adjustment of the height of the hand-grip means in accordance with the height of the user of the apparatus. Alternative forms of handgrip means may also be provided. There are preferably four sockets, two at each end of the platform and the hand grip means may comprise a single U-shaped member disposed at one end of the platform or two U-shaped members disposed one at each side of the platform.

The framework of the apparatus is conveniently formed from aluminium or steel

Best Available Copy

tubes and the rollers formed from a synthetic plastics material, for example nylon which may incorporate a lubricant, for example, molybdenum disulphide.

- 5 The invention will now be described by way of example with reference to the accompanying drawings in which:—

Figure 1 is a perspective view of an exercising apparatus,

- 10 Figure 2 is a side view of the apparatus showing an alternative form of hand-grip as compared of that shown in Figure 1, and

- Figure 3 is a plan view of the platform 15 of the apparatus without any form of hand-grip.

The apparatus shown in Figure 1 consists of a platform 10, a base 11 and a U-shaped hand-grip 12. The platform 10 includes a frame of rectangular form in plan view with a projecting lug 13 at each corner of the frame. Each lug 13 includes a flat base portion and an upwardly extending central socket 14, the socket 14 25 being of such dimensions that the ends of the legs 15 of the U-shaped hand grip 12 are close fits therein, the end portions of the legs 15 and the sockets 14 being provided with registering apertures (not shown) in which split pins 16 are fitted to hold the hand-grip firmly in position.

The frame of the platform 10 serves to support 22 rows of 12 rollers, each row of rollers being supported on a spindle which 35 has its ends mounted in a side member 17 of the frame and is supported intermediate its ends by passage through an opening in a centrally upstanding rib 18 forming part of the frame. The platform is formed as a metal casting and the rollers are of nylon loaded with a solid lubricant such as molybdenum disulphide whereby each of the rollers is independently and freely rotatable on its respective supporting spindle. When 45 a user of the apparatus is standing on the platform his weight is supported by the rollers and the platform 10 as a whole is mounted at an inclination to the horizontal so that the rollers will tend to rotate in a 50 direction such that eventually the person will effectively slide off the platform. It is accordingly necessary, for maintenance of his position that the user of the apparatus should walk or jog at a rate determined by 55 the inclination of the platform.

As previously explained, it is important that there should be a large number of rollers and that the rollers should be independently rotatable to allow for the different modes of movement of a person's 60 foot. The spindles on which the rollers are mounted are accordingly disposed one inch apart, the rollers being seven eighths of an inch in diameter and three quarters of an 65 inch long, with six rollers on each side of

the central rib 18. The platform 10 is formed as a casting and this rib 18 is formed integrally with the side and end members which form a peripheral frame around the rollers. The lugs 13 are also integral parts 70 of this casting.

The base 11 provides three horizontal steps; as shown in Figure 1 the platform 10 is supported on the lowermost step and the inclination of the platform to the 75 horizontal is at its minimum value. When the platform 10 is instead supported on the middle or uppermost step, the inclination of the platform to the horizontal is appropriately increased. In the particular embodiment shown in Figure 1, each step of the base 11 is provided with two spaced upstanding pins 19 which are arranged to locate in correspondingly spaced apertures 20 formed in the undersurface of the platform 10 adjacent one end thereof. The 85 particular pin and aperture arrangement that has been developed is of advantage in that it ensures that there are no projecting parts on the platform that might inadvertently be damaged or cause damage 90 to a floor covering.

Figure 1 shows an embodiment in which the U-shaped hand grip 12 is disposed at one end of the platform 10 with the lower 95 ends of its legs 15 fitting in the two sockets 14 at that end of the platform. In contrast therewith, Figure 2 shows an embodiment in which a hand grip 12 of slightly different configuration is employed 100 with the spacing between the legs 15 thereof increased sufficient to enable the lower ends thereof to fit in the two sockets 14 at one side of the platform. Two such hand grips are normally employed, i.e. one 105 at each side of the platform. For a relatively fit person taking exercises, the single hand grip of Figure 1 should be used whereas two hand grips, each as shown in Figure 2, are recommended for the elderly 110 and infirm.

Tread pads 21 may be provided at each end of the platform 10 as shown in Figure 1.

WHAT I CLAIM IS:—

1. Exercising apparatus comprising a 115 supporting framework including a platform and hand-grip means for gripping by a person standing on the platform, said platform having a presented surface afforded by a 120 multiplicity of rollers comprising a plurality of rows of independently rotatable rollers with each row of rollers containing a plurality of rollers and the rollers being arranged for rotation about substantially 125 horizontal axes.

2. Exercising apparatus according to claim 1, wherein all of the rollers are of uniform size.

3. Exercising apparatus according to 130

NOT AVAILABLE COPY

REPRODUCED FROM THE ORIGINAL

claim 1, wherein means are provided for adjusting the inclination of the platform to the horizontal.

4. Exercising apparatus according to claim 3, wherein the adjustment means comprises a stepped base which is provided with formations for engagement with cooperative formations on the underside of the platform.

5. Exercising apparatus according to claim 4, wherein the formations on the underside of the platform are apertures and the formations on the base are a plurality of projections on each step.

6. Exercising apparatus according to claim 1, wherein the hand-grip means comprises a generally U-shaped member having legs which clip into and are held within sockets disposed at one end of the platform.

7. Exercising apparatus according to claim 1, wherein the hand-grip means comprises two generally U-shaped members having legs which clip into and are held within sockets disposed at the two sides of

the platform.

8. Exercising apparatus according to claim 1, wherein the rollers are formed of a synthetic plastics material containing a lubricant.

9. Exercising apparatus according to claim 8, wherein the synthetic plastics material is nylon and the lubricant is molybdenum disulphide.

10. Exercising apparatus substantially as hereinbefore described with reference to and as shown in Figures 1 and 3 of the accompanying drawings.

11. Exercising apparatus substantially as hereinbefore described with reference to and as shown in Figures 2 and 3 of the accompanying drawings.

ARTHUR R. DAVIES,
Chartered Patent Agents,
27, Imperial Square,
Cheltenham,
— and —
115, High Holborn,
London, W.C.1.
Agents for the Applicant.

Printed for Her Majesty's Stationery Office by The Tweeddale Press Ltd., Berwick-upon-Tweed, 1977.
Published at the Patent Office, 25 Southampton Buildings, London, WC2A 1AY, from which copies may be obtained.

Best Available Copy


BEST AVAILABLE COPY

1495436

COMPLETE SPECIFICATION


3 SHEETS

This drawing is a reproduction of
the Original on a reduced scale.
SHEET 1



1 495 436 COMPLETE SPECIFICATION
3 SHEETS This drawing is a reproduction of
the Original on a reduced scale.
SHEET 2

—FIG.2—



Best Available Copy

BEST AVAILABLE COPY

1495436

COMPLETE SPECIFICATION

3 SHEETS

This drawing is a reproduction of
the Original on a reduced scale.
SHEET 3

